



## Premium Project Fix

High quality ceramic tile adhesive for projects.

### Uses

- For ceramic tiles.
- Tiling on smooth concrete surfaces, lightweight bricks, blocks, plaster boards.
- Tiling on wall surfaces that are plastered with water resistant plasters such as Vetonit Render & Vetonit Base WR on damp concrete interiors.
- Suitable for dry & wet conditions.

### Product Description

Fix Premium Project is a cementitious mortar adhesive composed of hydraulic binders, selected aggregates and special additives. It is supplied as a dry powder in pre-weighed bags ready to use on site, which requires only addition of clean water to produce easily workable mortar. Fix Premium Project is ideal for fixing of Ceramic Tiles, Terrazzo Tiles. Fix Premium Project is applied in thickness from 3mm to 10mm, depending upon type of tiles and quality of substrate. Fix Premium Project is available in white and grey colors.

### Advantages

- Factory controlled pre-blend ensures consistent high quality.
- Requires only addition of water on-site at the time of usage.
- Easy tile installation that enables high Productivity.
- Superior workability.
- Excellent Slip resistance.
- Excellent Adhesion on variety of tiles available in the local market.
- Water resistant
- Suitable for internal applications
- Suitable for horizontal & vertical surfaces.

### Standards Compliance

- BS:EN 12004 as C1T
- ISO 13007
- ASTM C348 & C349

### Technical Data

Fix Premium Project	Typical Values @ 25°C
Appearance	White Powder
Aggregate Size	1.35 max
Application Thickness	3 to 10 mm
Open Time	25 minutes
Adjustability	10 - 15 minutes
VOC	< 25 gm/Liter
EN12004 Classification	C1T
Compressive Strength @ 28 day (ASTM C349)	≥ 7.5 MPa
Flexural Strength @ 28 day (ASTM C348)	≥ 2.5 MPa
Tensile Adhesion (Bond Strength) @ 28 day (EN 1348)	≥ 0.7 MPa
Mixed Density	1.4 kg/liter ± 0.1 kg
Minimum application temperature	5°C

## Usage Instructions

### Surface Preparation

The surface should be sound, clean, free from loose material, grease, laitance, dirt, curing compound, etc.

Wet the all surfaces (except gypsum board) with clean water prior to the application of Fix Premium Project. Surface should appear damp with no water pooling.

### Mixing

For the preparation of mortar adhesive, pour into a container 14-16 liters of water for each 50 Kg bag of Fix Premium Project. Add the powder to the water and mix with a low speed electric drill fitted with a suitable paddle for 4-5 minutes, until a uniform, lump-free consistency is achieved. Allow the mixed material to stand for about 10 minutes and remix briefly with no further water to be added.

It can also be blended manually for small quantity but ensure correct amount of powder to water is maintained.

If required, add 0.5 Ltr of Vetobond AB432 to the mixing water followed by addition of powder.

Mixed material can be used within 2 hours.

Do not add water to the mix, once the mortar adhesive starts to harden.

### Application

Spread the mixed mortar adhesive and firmly pressed onto the surface to be tiled and work with notched trowel. Spread the mortar adhesive to an area that can be tiled within 10-15 minutes. Tiles are then firmly pressed over the mortar adhesive and immediately knocked into the desired position. Position of the tiles can be adjusted, if required, within its adjustability time of 10-15 minutes after installation. Allow the installed tiles to remain undisturbed for at least 48 hours. Mortar adhesive must not rise higher in the joints than halfway the thickness of the tiles. It is recommended to use Vetonit Tile Grout for filling the joint gaps after 2 days of tile installation.

### Cleaning

Tools and equipment can be cleaned with water immediately after use. Hardened materials will require removal by mechanical means.

## Packaging & Coverage

Product	Pack Size	Coverage
Fix Premium Project	50 Kg Bag	Walls: 12 – 13 m <sup>2</sup> /50kg bag Floor: 9 – 11 m <sup>2</sup> /50kg bag

Stated consumptions data are for general guidance. Actual consumption depends on the nature of substrate, method of application and wastages extra.

## Shelf Life & Storage

Original sealed container of Fix Project Premium has a shelf life of 12 months provided it is stored clear of ground in a dry shaded place below 25°C.

## Health & Safety

Fix Project Premium is highly alkaline therefore avoid direct contact with eyes or skin. It is recommended to use protective gloves and goggles during application. Any skin contact should be washed with soap & water. In case of eyes irritation, immediately wash with copious amount of clean cold water. Seek medical advice.

Fix Premium Project is non-flammable.

## Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications divided into the following product groups:

- Concrete Repair, Grouts and Enhancement.
- Wall & Facade Systems.
- Flooring and Coating Systems.
- Sealants and Joints.
- Plasters & Renders.
- Putties & Finishes.
- Tiling Systems
- Waterproofing.
- Primers & Ancillary Products.
- Specialty Products.

Saveto also provides various technical information such as CAD details, detailed method statements, specification clauses, application manuals, product selectors and technical support both in contractors and consultants offices as well as construction sites.

For further information on these products and systems kindly check our website or contact your local Saveto representative.

## LEGAL DISCLAIMER

Saveto endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Saveto has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of TDSs are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.