

# Vetotouch Sealer

Decorative protective sealer for cementitious finishes (Formally known as Vetotop AC444)

## Uses

- Sealing of Vetotouch range of cementitious decorative products.
- Semi Solid finish protection and sealing of cementitious facades.

## Product Description

Vetotouch Sealer is an environmentally friendly polymeric pore sealer for Vetotouch range of decorative products. The product seals the surface finish to protect against contaminants and water ingress.

## Advantages

- Easily applied by roll or airless-spray.
- Protects against contaminants and water ingress.
- Designed to work with cementitious finishes and Vetotouch range of products.
- Cost effective, suitable for use in MENA region weathering conditions.

## Design Criteria

Designed to work with Vetotouch range of cementitious decorative products. The application is designed to a 2 - 3 coats at a rate of 3 to 6 m<sup>2</sup> per liter per coat to achieve best results and closing the substrate surface. The coverage rate may decrease or increase depending on the porosity of the substrate and its texture.

Note: You can dilute by water up to 15% if required.

## Technical Data

Vetotouch Sealer	Typical Values @ 20°C
Dry Appearance	Semi-Solid
Appearance	Colored liquid
Number of Coats	2 - 3*
Dry Time (25°C & RH50%)	45 minutes
Best Application Technique	Roller
Practical Coverage	3 - 6 m <sup>2</sup> / liter/ coat*

\* Depends on surface texture, surface absorption and desired color depth.

## Usage Instructions

### Surface Preparation

Surface must be sound and thoroughly cleaned by compressed air before Vetotouch Sealer is applied.

### Application

Vetotouch Sealer should be applied as a continuous flood coat using either a soft brush or low pressure spray equipment at the correct coverage rate. For best performance apply a flood of 2 - 3 coats at rate 3 - 6 m<sup>2</sup> per liter per coat

## Cleaning

Equipment and tools can be cleaned using clean water immediately after use. Shall residual material exist or harden, mechanical means such as wire brush would be required to remove residue.

## Packaging & Coverage

Product	Pack Size	Theoretical Coverage
Vetotouch Sealer	20 Liter Pail	3 - 6 m <sup>2</sup> / liter/ coat

Stated consumptions data are for general guidance. Actual consumption depends on the nature of substrate, method of application and wastage.

## Shelf Life & Storage

Original sealed containers of Vetotouch Sealer has a shelf life of 12 months provided it is stored clear of ground in a dry and shaded place below 35°C.

## Health & Safety

Vetotouch Sealer should not come into contact with skin and eyes or be swallowed. Avoid inhalation of vapor and spray. Use only in well ventilated areas. In case of insufficient ventilation wear suitable respiratory protection.

Wear suitable protective clothing, gloves and eye/ face protection. Barrier creams provide additional skin protection.

Should accidental skin contact occur, remove immediately with a suitable skin cleanser followed by washing with soap and water.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed, seek medical attention immediately - do not induce vomiting.

Refer to Material Safety Data Sheet for further information.

## Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications divided into the following product groups:

- Waterproofing.
- Concrete Repairs, Grouts and Enhancement.
- Flooring and Coating Systems.
- Wall & Facade Systems.
- Sealants and Joints.
- Renders & Finishes.
- Plasters & Masonry.
- Tiling Systems.
- Primers & Ancillary Products.
- Specialty Products.

Saveto also provides various technical information such as CAD details, detailed method statements, specification clauses, application manuals, product selectors and technical support both in contractors and consultants offices as well as construction sites.

For further information on these products and systems kindly check our website or contact your local Saveto representative.

## LEGAL DISCLAIMER

Saveto endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Saveto has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of TDSs are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.