



Vetotop CS535

Premixed 10 to 30 mm thick cementitious screed.

Uses

- Leveling of concrete slabs prior to application of final floor coverings.
- Screeding over hollow-core pre-cast concrete slabs.
- Leveling floors and slabs to slope to ensure proper flow to drains.

Product Description

Vetotop CS535 is a single component cementitious floor screed composed of hydraulic binders, silica sand, selected aggregates special additives and fibers. It is supplied as a dry powder in pre-weighed bags ready to use on site, once mixed it will form a trowellable mortar that is applied in thicknesses between 10 and 30 mm.

Advantages

- Factory controlled pre-blend ensures consistent high quality.
- Suitable for Middle East harsh weather conditions.
- Easy application enabling high productivity & superior finishing.
- High bond to substrate.
- Excellent physical and mechanical properties.
- Shrinkage compensated.
- Excellent workability.
- Fiber reinforced resisting crack formation.

Standards Compliance

- EN197: 2011
- EN16236:2013
- EN13813:2002
- BS8204:2010

Technical Data

Vetotop CS535	Typical Values
Appearance	Grey color powder
Aggregate size (mm)	0-3 mm
Application thickness	10 - 30 mm
Dry density (Kg/Liter)	1.70 approx.
Wet density (Kg/Liter)	2.10 approx.
Open time @ 25°C	30 min approx.
Compressive Strength @ 28 days (ASTM C349)	40 N/mm ² approx.
Water demand	13 - 16%

Usage Instructions

Surface Preparation

The surface should be sound, clean, free from loose material, grease, laitance, dirt curing compound, etc.

Priming

Vetotop CS535 can be laid as a bonded screed by applying Vetobond PB434 slurry to prepared concrete substrate as a bonding and priming layer, alternatively and epoxy bonding agent can be used such as Vetobond EB430 or EB431.

To prepare the slurry primer mix 1 volume of VetoBond PB434 to 1 volume of clean water with 3 volumes of fresh cement and mix until a smooth consistency is

prepared. Scrub the mixed slurry into the concrete surface, while the slurry is wet apply Vetotop CS535 in order to ensure good adhesion with the substrate.

Application

For the preparation of mixture, pour into a container 6.5-8 liters of water for 50 Kg bag of Vetotop CS535.

Add the powder to the water and mix with a low speed electric drill fitted with a suitable paddle, until a uniform, lump free consistency mix is achieved. No further water should be added to the mix. Do not add water to the mix once its start to set.

Add the required aggregate type to the mixed screed slowly while continuing mixing until a uniform consistency as achieved.

Pour the mixed product onto the surface and spread to the desired thickness using steel trowel or suitable tools.

Cure the screed as per standard concrete curing practices. Do not subject the screed to vehicular traffic for 28 days till ensure full cure and systems ability to withstand designed traffic loads.

A concrete sealer is required for enhancing the screed durability and resistance to ingress of water, apply Vetoseal XW770 at a rate of 8 to 12 m² per liter. Make sure that the sealer is uniformly applied and covering all screed surface.

Cleaning

Clean tools with water promptly before material hardens. Hardened material can be mechanically removed.

Packaging & Coverage

Product	Pack Size	Yield
Vetotop CS535	50 Kg Bag	23.3 - 32.3 Ltr

Stated consumptions data are for general guidance. Actual consumption depends on the nature of substrate, method of application and wastage.

Shelf Life & Storage

Original sealed bag of Vetotop CS535 has a shelf life of 12 months provided it is stored clear of ground in a dry and shaded place below 35°C

Limitations

- Do not apply the product at temperature less than +5°C.
- For further information contact our technical department.

Health & Safety

Vetotop CS535 is highly alkaline therefore avoid direct contact with eyes or skin. Vetobond PB434 is latex emulsion. It is recommended to use protective gloves and goggles during application.

Any skin contact should be washed with plenty amount of water. In case of eyes irritation, immediately wash with copious amount of clean cold water. Seek medical advice.

Vetotop CS535 is non-flammable.

LEGAL DISCLAIMER

Saveto endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Saveto has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of TDSs are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.