



## Vetotouch Sealer

Decorative protective sealer for cementitious finishes

(Formally known as Vetotop AC444)

### Uses

- Sealing of Vetotouch range of cementitious decorative products.
- Finish protection and sealing of cementitious facades.

### Product Description

Vetotouch Sealer is an environmentally friendly polymeric pore sealer for the decorative products of the Saveto Vetotouch range. The product seals the surface finish to protect against contaminants and water ingress.

### Advantages

- Easily applied by the roll or airless spray.
- Protects against contaminants and water ingress.
- Designed to work with cementitious finishes and Vetotouch range of products.
- Cost effective, suitable for use in MENA region weathering conditions.

### Technical Data

Vetotouch Sealer	Typical Values @ 25 °C & RH 50%
Appearance	Colored liquid
Number of Coats	2 - 3*
Density (kg/ltr)	1.3
Solid Content (weight%)	52 ± 2
Dry Time (Minutes)	45
Best Application Technique	Roller

### Standards Compliance

- EN 1504-2

### Design Criteria

Designed to work with Vetotouch range of cementitious decorative products. The application is designed for 2 - 3 coats at a rate of 3 m<sup>2</sup> per liter per coat to achieve the best results of closing the substrate surface. The coverage rate may decrease or increase depending on the porosity of the substrate and its texture.

Note: You can dilute by water up to 15% if required.

## Usage Instructions

### Surface Preparation

The surface must be sound and thoroughly clean by compressed air before applying Vetotouch Sealer.

### Application

Apply Vetotouch Sealer as a continuous flood coat using either a soft brush or low-pressure spray equipment at the correct coverage rate. For best performance, apply a flood of 2 - 3 coats at 3 m<sup>2</sup> per liter per coat.

### Cleaning

Clean equipment and tools using clean water immediately after use. If residual material exists or hardens, mechanical means such as wire brush would be required to remove residue.

## Packaging & Coverage

Product	Pack Size	Coverage
Vetotouch Sealer	20 Liter Container	3 m <sup>2</sup> /liter/coat @ 200 microns

Stated consumption data are for general guidance. Actual consumption depends on the nature of substrate, consistency used, method of application, and wastage.

### Shelf Life & Storage

The original sealed container of Vetotouch Sealer has a shelf life of 12 months, provided it is stored clear of ground in a dry and shaded place below 35°C.

### Health & Safety

Vetotouch Sealer should not come into contact with skin and eyes or be swallowed. Avoid inhalation of vapor and spray. Use only in well-ventilated areas. In case of insufficient ventilation, wear suitable respiratory protection.

Wear suitable protective clothing, gloves, and eye/ face protection. Barrier creams provide additional skin protection.

Should accidental skin contact occur, remove immediately with a suitable skin cleanser followed by washing with soap and water.

In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed, seek medical attention immediately - do not induce vomiting.

Refer to Material Safety Data Sheet for further information.

### Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.

## Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.