



Vetobond 303

Solvent Based Carpet Adhesive

Uses

- Vetobond 303 is recommended for bonding of carpet backings with various substrates.

Product Description

Vetobond 303 is a high coverage, one component contact adhesive based on Polychloroprene Rubber with special tackifier and additives. Vetobond 303 is specially developed for being compatible with most of the substrates. Vetobond 303 is very good in film forming nature which gives uniform bonding to many surfaces.

Advantages

- Excellent adhesion and high strength.
- Excellent bonding to porous and non-porous surfaces.
- Compatible with most carpet backings.
- Permanently flexible and very strong.
- Excellent chemical resistance.
- Excellent heat resistance.
- Fast drying.
- Low odor.

Technical Data

Vetobond 303	Typical Values @ 25°C
Appearance	Yellow Liquid
Application temperature (°C)	15 to 35
Full Dry time	24 Hours recommended
Specific gravity (kg/ltr)	0.86 ± 0.05
Viscosity (cPs)	1500 - 2200
Solid content (%)	31 ± 2

Standards Compliance

- Free of asbestos, lead and mercury compounds

Usage Instructions

Surface Preparation

The surface should be structurally sound, clean, dry, leveled and free from dust, curing compounds, grease and other loose debris. Keep container closed when not in use.

Application

Apply Vetobond 303 evenly with brush or roller evenly on both surfaces and wait until solvent has fully evaporated.

After the evaporation of solvent in adhesive, assemble the surface by applying

After the evaporation of solvent in adhesive, assemble the surface by applying normal hand pressure. Special care must be taken on the edges and adhesive must be evenly applied.

Cleaning

Clean with carbon solvent only.

Packaging & Coverage

Product	Pack Size	Open Time	Coverage
Vetobond 303	650 ml and 1 USG Metal Can	10-25 Minutes	3 - 6 m ² /ltr (subject to surface condition)

Stated consumption data are for general guidance. Actual consumption depends on the nature of substrate, method of application, and wastage.

Shelf Life & Storage

12 months from date of manufacturing in original unopened containers.

Store under cover, protect from direct sunlight and high temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. Recommended to store between 15°C to 30°C.

Health & Safety

As with all chemicals, caution should always be exercised. Consult Material Safety Data Sheet and container label for further information.

Additional Information

Saveto manufactures a wide range of construction chemicals and speciality products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.

Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.