



Vetobond PB433

Resin adhesive, cement modifier, bonding agent, & sealer

Uses

- As a universal & versatile general adhesive.
- As a primer on bituminous material used for painting with oil-based paints.
- As a plaster bonding aid for tile & granolithic concrete toppings.
- As a dust proofer for cementitious surfaces.
- As an admixture to cement-based products.

Product Description

Vetobond PB433 is a polyvinyl acetate (PVAc)-based bonding agent. The cement admixture, a non-toxic, non-flammable liquid of medium viscosity, dries to a transparent film sealer and cement modifier designed to be used as a low gauging liquid cementitious system. It can be used for internal applications as well.

Apply Vetobond PB433 directly from the bottle or pail using a brush, a roller, or spraying equipment onto the concrete substrate.

Advantages

- Versatile (Can be used for various applications in many building trades).
- Environmentally friendly (water-based, odorless, and non-flammable).
- Suitable for use over bituminous materials.
- Easy to apply by brush, roller, or spray.
- Excellent bond to most construction materials.
- Cost-effective
- Suitable for the weather conditions of the MENA region.

General Applications

Vetobond PB433 has the following general areas of application:

- As a cement modifier; it enhances the adhesion of cement-based products to concrete and other masonry products.
- As a primer for gypsum boards and plasters receiving paints.
- To repair cracks & holes in cementitious floors.
- To resurface worn concrete & granolithic floors.
- To level worn stair treads.

Technical Data

Vetobond PB433	Typical Values @ 22°C
Appearance	White liquid
Density (kg/L)	~ 1
pH Level	8.5
voc (g/L)	< 15

Standards Compliance

- ASTM D4317

Usage Instructions

Surface Preparation

The surface must be sound and thoroughly cleaned before Vetobond PB433 is applied. All loose particles, old mortar, laitance, dirt, paint, etc., must be removed by brushing with a stiff /wire brush (or other suitable method).

Fungi or Algae should be scoured away using a hypochlorite-type bleach or a proprietary fungicidal solution. Then it must be washed with water.

Timber and composition boarding must be dry and free from wax, polish, and paint, etc. Remove all traces of oil and grease with an industrial-grade chemical degreaser or another suitable degreasing agent.

BONDING AGENTS AND PRIMERS

On vertical surfaces (where the paint cannot be removed), it is advisable to peck-hammer (except when planning to apply gypsum plasters). This ensures a bond between Vetobond PB433 and the structure and prevents failure due to lack of adhesion between the paint film and the substrate.

Sealing Porous Surfaces

Porous surfaces should be sealed with a solution of 1 part Vetobond PB433 without dilution. If the surface is less absorbent, then dilution of up to 1 part PB433 to 10 part clean water.

Site trials are highly recommended before dilution. Breeze, foam, slag, and other lightweight building blocks are exceptionally absorbent and may require wetting down before sealing.

Other Applications

- As a plaster bonding agent: For Gypsum, lightweight gypsum, and Anhydrous plasters, seal as you're required & prime with a solution of 1 part Vetobond PB433 to 1 part water. Allow it to become tacky, then plaster normally & straight onto the tacky Vetobond PB433.
- For heavier rendering & cementitious toppings: Seal and prime as above, then prepare a key coat by mixing 1 part ordinary Portland cement, 1 part clean washed sharp sand, gauged to a stiff consistency with 1 part Vetobond PB433 to 3 parts clean water. Apply this to the tacky priming coat at an average thickness of 6 mm (¼ inch) and stipple with a stiff brush or otherwise roughen the surface to provide a good mechanical key. Allow to harden and dry thoroughly. Test for adhesion before applying on render.
- Ceramic, concrete, quarry, clay, and terrazzo tiles: Seal with a solution of 1 part Vetobond PB433 to 5 parts water. Brush the material well into the surface and allow it to dry. Before bedding tiles in sand and cement, apply another coat (3 parts Vetobond PB433 to 1 part water) onto the floor and the base of the tile. And while it is still wet or tacky, apply sand and cement bedding to both the base & bed the tiles.
- Polystyrene tiles, plasterboard and acoustic board: Prepare and seal the surfaces where required. Using a suitable filler such as plaster, cement, fine sand, or sawdust, make a paste with the solution of 1 part Vetobond PB433 to 1 part water. Apply this mixture as an adhesive coat to the tiles and surface you're bonding.

Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.

Packaging

Product	Pack Size
Vetobond PB433	20 Liters Pail 200 Liters Drum

Coverage

Usage	Vetobond PB433	Water	M ² (Approx.)
Sealer Coat	1	10	50
	1	5	25
Primer Coat	1	1	15
Primer in Conjunction with Mortar	1	1	3
	1	3	3

Note: These figures are based on typical substrates. Actual coverage may vary according to porosity.

Shelf Life & Storage

The original sealed container of Vetobond PB433 has a shelf life of 12 months, provided it is stored at a temperature below 35°C.

Health & Safety

Vetobond PB433 is non-flammable. Kindly refer to the product MSDS for more information.

Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.