



Vetotop UC373

Line marking polyurethane coating for traffic

Uses

- As a line marking paint with Vetotop range of products or car park deck coating systems.
- General epoxy and polyurethane coated decks
- Car park flooring
- Concrete surface in factories, warehouses and car parks
- Playground and sport flooring
- Kerb stones and stair, treads

Product Description

Vetotop UC373 is a specially formulated fast drying line marking paint that can be applied in one coat for marking lines on concrete, epoxy or polyurethane surfaces. Vetotop UC373 paint is based on Polyester-Polyurethane

Advantages

- Suitable for exterior and interior applications
- Quick drying
- Excellent resistance against water, oil, alkalis and hydrocarbon fuels
- Good adhesion to concrete, epoxy and polyurethane coatings
- Durable with excellent abrasion resistance
- Good reflection properties when mixed with glass beads

Standards Compliance

- DIN 53457
- BS EN476:2009 as class 1 in flame spread.

Technical Data

Vetotop UC373	Typical Values
Appearance	Liquid
Color	5 Colors:
	1023
	3020
	5017
	6024
	9016
Mix Density at 25°C	1.45 kg /L
Solid Content	65%
Touch dry at 25°C	3 Hours
Application Temperature	5°C to 35°C
Recommend minimum dry film thickness	100 microns

Note: All values are subject to 5-10 % tolerance

Usage Instructions

Surface Preparation

The surface should be sound, clean, dry and free from loose material, laitance, dirt, oil, grease or any other contaminants. If needed, wash the surface with detergent and then with clean water. Allow to dry completely before application. Do not use solvent to clean the surface before applying the product.

Mixing

Mix the contents of the container thoroughly before application.

Application

Vetotop UC373 can be applied with brush, roller or airless spray gun. It may be needed to dilute the product with 5 to 10% Vetonit Solvent XX300, If airless spray gun is used. The nozzle tip of the gun should be from 4-6 mm. Apply the paint with a pressure of 30-40 psi.

Apply Vetotop UC373 at a rate of 5m²/Liter (200 microns wet). If another coat is needed to build up the thickness, then apply the second coat after the first one is totally dry.

For the light reflection, proper glass beads with size <200 microns can be sprinkled on top of the applied coating while it is still wet.

Cleaning

Clean tools with Vetonit Solvent XX300 promptly before material hardens. Cured material must be mechanically removed.

Packaging & Coverage

Product	Pack Size	Coverage
Vetotop UC373	1 & 4 Liter	5-6 m ² / Liter

Stated consumptions data are for general guidance. Actual consumption depends on the nature of substrate, method of application and wastage.

In case of use of antislip aggregates, the consumption values for the top coat will be reduced by 15 - 20%.

Shelf Life & Storage

Original sealed kit of Vetotop UC373 has a shelf life of 12 months provided it is stored clear of ground in a dry and shaded place below 35°C.

Keep the product in tightly closed containers stored in dry covered place, at a temperature not less than +5°C and not more than +35°C. Under these conditions, the product will have a shelf life of 12 months.

Limitations

Do not apply the paint during rainy or stormy weather or when humidity is greater than 80%

Health & Safety

During application, wear appropriate protective clothing, goggles, gloves and respiratory equipment if necessary.

In case of contact with skin, rinse with water and again wash thoroughly with soap and water. In case of contact with eyes, rinse with plenty of water and seek medical advice accordingly.

If ingested, obtain medical attention immediately. Do not induce vomiting.

Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications divided into the following product groups:

- Waterproofing.
- Concrete Repairs, Grouts and Enhancements.
- Flooring and Coating Systems.
- Wall & Facade Systems.
- Sealants and Joints.
- Renders & Finishes.
- Plasters & Masonry.
- Tiling Systems.
- Primers & Ancillary Products.
- Specialty Products.

LEGAL DISCLAIMER

Saveto endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Saveto has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of TDSs are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.